SKU: 21712-B

UPC:

Features & Benefits:

Description: Heat Shrinkable Tubing, Heavy Wall, 2in Expanded ID, Conductor Range 1000-500, 12in Tube, Black, Bag of 1

Specs

Additional Class Attributes

Container	NA
Model	Tube
Shrink Ratio	3:1

Dimensions

Cut Length	12 in
Expanded ID (IN)	2
Expanded ID (mm)	50.8
Height (IN)	0
Height BX (IN)	6.75
Length (IN)	0
Recovered ID (IN)	0.750 IN
Recovered Wall Thickness (IN)	0.155 IN
Weight (LB)	0.2813
Weight BX (LB)	3.363
Width (IN)	0
Width BX (IN)	14

Additional Technical Specifications

Dielectric Strength	500 V/Mil

Material and Finish

Material	Polyolefin

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
NEMA Code	0-000-1
UPC Code	78366942043

Testing Standards

CSA File Number	AP-100973-1
CSA Standard	C22.2 No. 198.2
Mil Spec #	AMS-DTL-23053/15 CLASS 1
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	8M24
UL / CULUS Specification	UL 486D Listed
UL File Number	E158587

Environment and Temperature

Flammability Rating	Flame Retardant per Mil Spec 23053/15
Minimum Shrink Temperature	120°C
Operating Temperature	-55°C to 100°C
Temperature Rating	-55°C to 100°C

Color

Color	Black

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	1000 kcmil - 500 kcmil
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1000 kcmil - 500 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	600 V