




SKU: 24003-B10

UPC:

Features & Benefits:

Description:Heat Shrinkable Tubing, Thin Wall, 3/32in Expanded ID, Conductor Range 22-28, 6in Disk, Black, Bag of 10

Specs

Additional Class Attributes

Container	Disk dispenser
Model	Tube
Shrink Ratio	2:1

Dimensions

Cut Length	6 in
Expanded ID (IN)	0.093
Expanded ID (mm)	2.3622
Height (IN)	0
Height BX (IN)	2.75
Length (IN)	0
Recovered ID (IN)	0.046 IN
Recovered Wall Thickness (IN)	0.020 IN
Weight (LB)	0.1086
Weight BX (LB)	1.333
Width (IN)	0
Width BX (IN)	6

Additional Technical Specifications

Dielectric Strength	600 V/Mil
---------------------	-----------

Material and Finish

Material	Polyolefin
----------	------------

General

Bag Quantity	10
Carton Quantity Description	STD PACK QTY 10
NEMA Code	0-000-1
UPC Code	78366971307

Testing Standards



CSA File Number	AP-100973-1
CSA Standard	C22.2 No. 198.1
Mil Spec #	AMS-DTL-23053/5 CLASS 1
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
RUS Listed	Yes
UL / CULUS Specification	UL 224 Recognized
UL File Number	E158587

Environment and Temperature

Flammability Rating	NA
Minimum Shrink Temperature	90°C
Operating Temperature	-55°C to 135°C
Temperature Rating	-55°C to 135°C

Color

Color	Black
-------	-------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	22 Sol - 28 Sol
Conductor Range AL Stranded (Primary, run, main, line)	22 Str - 28 Str
Conductor Range AL Stranded (Secondary, tap, load)	22 Str - 28 Str
Conductor Range CU Solid (Primary, run, main, line)	22 Sol - 28 Sol
Conductor Range CU Solid (Secondary, tap, load)	22 Sol - 28 Sol
Conductor Range CU Stranded (Primary, run, main, line)	22 Str - 28 Str
Conductor Range CU Stranded (Secondary, tap, load)	22 Str - 28 Str
Conductor Range AL Solid (Primary, run, main, line)	22 Sol - 28 Sol

Voltage

Voltage Rating	600 V
----------------	-------