SKU: 24010-B5

UPC:

Features & Benefits:

Description: Heat Shrinkable Tubing, Thin Wall, 3/4in Expanded ID, Conductor Range 2/0-2, 6in Disk, Black, Bag of 5

Specs

Additional Class Attributes

Container	Disk dispenser
Model	Tube
Shrink Ratio	2:1

Dimensions

Cut Length	6 in
Expanded ID (IN)	0.75
Expanded ID (mm)	19.05
Height (IN)	0
Height BX (IN)	2.75
Length (IN)	0
Recovered ID (IN)	0.375 IN
Recovered Wall Thickness (IN)	0.030 IN
Weight (LB)	0.1446
Weight BX (LB)	1.693
Width (IN)	0
Width BX (IN)	6

Additional Technical Specifications

Dielectric Strength	600 V/Mil

Material and Finish

Material	Polyolefin

General

Bag Quantity	5
Carton Quantity Description	STD PACK QTY 10
NEMA Code	0-000-1
UPC Code	78366971314

Testing Standards

CSA File Number	AP-100973-1
CSA Standard	C22.2 No. 198.1
Mil Spec #	AMS-DTL-23053/5 CLASS 1
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
RUS Listed	Yes
UL / CULUS Specification	UL 224 Recognized
UL File Number	E158587

Environment and Temperature

Flammability Rating	NA
Minimum Shrink Temperature	90°C
Operating Temperature	-55°C to 135°C
Temperature Rating	-55°C to 135°C

Color

Color	Black

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	2/0 Str - 2 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str - 2 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	600 V