



SKU: 25002

UPC: 0783669421026

Features & Benefits:

Description:Heat Shrinkable Tubing, Thin Wall, 1/16in Expanded ID, Conductor Range 24-30, 8ft Disk, Black

Specs

Additional Class Attributes

Container	Disk dispenser
Model	Tube
Shrink Ratio	2:1

Dimensions

Cut Length	96 in
Expanded ID (IN)	0.063
Expanded ID (mm)	1.6002
Height (IN)	0.048
Height BX (IN)	5.25
Length (IN)	96
Recovered ID (IN)	0.031 IN
Recovered Wall Thickness (IN)	0.017 IN
Weight (LB)	0.7
Weight BX (LB)	7
Width (IN)	0.048
Width BX (IN)	7.25

Additional Technical Specifications

Dielectric Strength	600 V/Mil
---------------------	-----------

Material and Finish

Material	Polyolefin
----------	------------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
NEMA Code	0-000-1
UPC Code	78366942102

Testing Standards



CSA File Number	AP-100973-1
CSA Standard	C22.2 No. 198.1
Mil Spec #	AMS-DTL-23053/5 CLASS 1
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
RUS Listed	Yes
UL / CULUS Specification	UL 224 Recognized
UL File Number	E158587

Environment and Temperature

Flammability Rating	NA
Minimum Shrink Temperature	90°C
Operating Temperature	-55°C to 135°C
Temperature Rating	-55°C to 135°C

Color

Color	Black
-------	-------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	24 Str - 30 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	24 Sol - 30 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	24 Str - 30 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	24 Sol - 30 Sol

Voltage

Voltage Rating	600 V
----------------	-------