



SKU: 26011

UPC: 0783669421866

Features & Benefits:

Description:Heat Shrinkable Tubing, Thin Wall, 1in Expanded ID, Conductor Range 4/0-1, 200ft Spool, Black

Specs

Additional Class Attributes

Container	Spool
Model	Tube
Shrink Ratio	2:1

Dimensions

Cut Length	200 ft
Expanded ID (IN)	1
Expanded ID (mm)	25.4
Length (IN)	200
Length (mm)	5080
Recovered ID (IN)	0.500 IN
Recovered Wall Thickness (IN)	0.035 IN

Additional Technical Specifications

Dielectric Strength	600 V/Mil
---------------------	-----------

Material and Finish

Material	Polyolefin
----------	------------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
NEMA Code	0-000-1
UPC Code	78366942186

Testing Standards

CSA File Number	AP-100973-1
CSA Standard	C22.2 No. 198.1
Mil Spec #	AMS-DTL-23053/5 CLASS 1
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation



RUS Listed

Yes

UL / CULUS Specification

UL 224 Recognized

UL File Number

E158587

Environment and Temperature

Flammability Rating

NA

Minimum Shrink Temperature

90°C

Operating Temperature

-55°C to 135°C

Temperature Rating

-55°C to 135°C

Color

Color

Black

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

4/0 Str - 1 Str

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

NA

Conductor Range CU Solid (Secondary, tap, load)

NA

Conductor Range CU Stranded (Primary, run, main, line)

4/0 Str - 1 Str

Conductor Range CU Stranded (Secondary, tap, load)

NA

Conductor Range AL Solid (Primary, run, main, line)

NA

Voltage

Voltage Rating

600 V