SKU: 44131-B10

UPC:

Features & Benefits:

Description:ILSCON Ring Terminal, Conductor Size 8, 1/4in Bolt Size, Non-Insulated, Pack of 10

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Brazed
Insulation Flared End	No
Insulation Grip	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Tongue Type	Ring

Dimensions

Height (IN)	0
Height BX (IN)	2
Length (IN)	0
Weight (LB)	0.145
Weight BX (LB)	1.597
Width (IN)	0
Width BX (IN)	6.1875

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation	None
Material	Copper

General

Bag Quantity	10
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366944157

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/4

Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL File Number	NA

Color

Color	Silver

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	8 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Environment and Temperature

Halogen Free	NA
Temperature Rating	90°C