



SKU: 44160-B10

UPC:



Features & Benefits:

Description:ILSCON Ring Terminal, Conductor Size 2, #10 Bolt Size, Non-Insulated, Pack of 10

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Brazed
Insulation Flared End	No
Insulation Grip	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Tongue Type	Ring

Dimensions

Height (IN)	0
Height BX (IN)	2
Length (IN)	0
Mounting Bolt/Stud Size (mm)	254
Weight (LB)	0.365
Weight BX (LB)	3.797
Width (IN)	0
Width BX (IN)	6.1875

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation	None
Material	Copper

General

Bag Quantity	10
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366944179



Bolt and Screw Sizes

Mounting Bolt/Stud Size

#10

Testing Standards

Prop65 Compliance

This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

UL Control Number

NA

UL File Number

NA

Color

Color

Silver

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load) NA

Conductor Range AL Stranded (Primary, run, main, line) NA

Conductor Range AL Stranded (Secondary, tap, load) NA

Conductor Range CU Solid (Primary, run, main, line) NA

Conductor Range CU Solid (Secondary, tap, load) NA

Conductor Range CU Stranded (Primary, run, main, line) 2 Str

Conductor Range CU Stranded (Secondary, tap, load) NA

Conductor Range AL Solid (Primary, run, main, line) NA

Environment and Temperature

Halogen Free

NA

Temperature Rating

90°C