



**SKU:** 44213-B10

**UPC:**

**Features & Benefits:**

**Description:**ILSCON Ring Terminal, Conductor Range 14-16, #10 Bolt Size, Vinyl Insulated, Blue Color Code, Pack of 10

## Specs

### Additional Class Attributes

|                          |             |
|--------------------------|-------------|
| Conductor Entry          | Funnel wire |
| Connection               | Compression |
| Construction Type        | Brazed      |
| Insulation Flared End    | Yes         |
| Insulation Grip          | Yes         |
| Mounting Hole Type       | Thru        |
| Number of Conductors     | 1           |
| Number of Mounting Holes | 1           |
| Tongue Type              | Ring        |

### Dimensions

|                                       |        |
|---------------------------------------|--------|
| Height (IN)                           | 0      |
| Height BX (IN)                        | 2      |
| Length (IN)                           | 0      |
| Maximum Wire Insulation Diameter (IN) | 0.175  |
| Mounting Bolt/Stud Size (mm)          | 254    |
| Weight (LB)                           | 0.087  |
| Weight BX (LB)                        | 1.017  |
| Width (IN)                            | 0      |
| Width BX (IN)                         | 6.1875 |

### Material and Finish

|                    |        |
|--------------------|--------|
| Conductor Material | Copper |
| Connector Finish   | Tin    |
| Fully Insulated    | No     |
| Insulation         | Vinyl  |
| Material           | Copper |

### General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 10              |
| Carton Quantity Description | STD PACK QTY 10 |
| Dual Rated                  | No              |
| NEMA Code                   | S-588-3         |
| UPC Code                    | 78366944260     |



### ***Bolt and Screw Sizes***

Mounting Bolt/Stud Size

#10

### ***Testing Standards***

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -  
[www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

UL Control Number

NA

UL File Number

NA

### ***Color***

Color

Silver

Color Code

Blue

### ***Conductor Ranges***

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

NA

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

14 Sol - 16 Sol

Conductor Range CU Solid (Secondary, tap, load)

NA

Conductor Range CU Stranded (Primary, run, main, line)

14 Str - 16 Str

Conductor Range CU Stranded (Secondary, tap, load)

NA

Conductor Range AL Solid (Primary, run, main, line)

NA

### ***Voltage***

Voltage Rating

600 V

### ***Environment and Temperature***

Halogen Free

No

Temperature Rating

90°C