



SKU: 44226-B10

UPC:

Features & Benefits:

Description:ILSCON Ring Terminal, Conductor Range 10-12, 1/2in Bolt Size, Vinyl Insulated, Yellow Color Code, Pack of 10

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Brazed
Insulation Flared End	Yes
Insulation Grip	Yes
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Tongue Type	Ring

Dimensions

Height (IN)	0
Height BX (IN)	2
Length (IN)	0
Maximum Wire Insulation Diameter (IN)	0.255
Mounting Bolt/Stud Size (mm)	304.8
Weight (LB)	0.121
Weight BX (LB)	1.357
Width (IN)	0
Width BX (IN)	6.1875

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation	Vinyl
Material	Copper

General

Bag Quantity	10
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366944270



Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	NA
UL File Number	NA

Color

Color	Silver
Color Code	Yellow

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 12 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	10 Str - 12 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	600 V
----------------	-------

Environment and Temperature

Halogen Free	No
Temperature Rating	90°C