



SKU: 44710-B10

UPC:

Features & Benefits:

Description:ILSCON Parallel Splice, Conductor Range 14-16, Vinyl Insulated, Blue Color Code, Bag of 10

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Connector Type	Parallel Splice
Construction Type	Brazed
Insulation Flared End	Yes
Mounting Hole Type	NA
Number of Conductors	2

Dimensions

Height (IN)	0
Height BX (IN)	2
Length (IN)	0.76
Length (mm)	19.304
Maximum Wire Insulation Diameter (IN)	NA
Weight (LB)	0.105
Weight BX (LB)	1.197
Width (IN)	0
Width BX (IN)	6.1875

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	Yes
Insulation	Vinyl
Material	Copper

General

Bag Quantity	10
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366944341



Bolt and Screw Sizes

Mounting Bolt/Stud Size

NA

Testing Standards

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -
www.P65warnings.ca.gov

UL Control Number

NA

UL File Number

NA

Color

Color

Silver

Color Code

Blue

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

NA

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

14 Sol - 16 Sol

Conductor Range CU Solid (Secondary, tap, load)

NA

Conductor Range CU Stranded (Primary, run, main, line)

14 Str - 16 Str

Conductor Range CU Stranded (Secondary, tap, load)

NA

Conductor Range AL Solid (Primary, run, main, line)

NA

Voltage

Voltage Rating

600 V

Environment and Temperature

Halogen Free

No

Temperature Rating

90°C