

SKU: 44900-B10

UPC:

Features & Benefits:

Description:ILSCON Butt Splice, Conductor Range 18-22, Vinyl Insulated, Red Color Code, Bag of 10

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Connector Type	Parallel Splice
Construction Type	Brazed
Insulation Flared End	Yes
Mounting Hole Type	NA
Number of Conductors	2

Dimensions

Height (IN)	0
Height BX (IN)	2
Length (IN)	0.95
Length (mm)	24.13
Maximum Wire Insulation Diameter (IN)	0.385
Weight (LB)	0.115
Weight BX (LB)	1.297
Width (IN)	0
Width BX (IN)	6.1875

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	Yes
Insulation	Vinyl
Material	Copper

General

Bag Quantity	10
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366944352

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	NA
UL File Number	NA

Color

Color	Silver
Color Code	Red

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	18 Sol - 22 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	18 Str - 22 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	600 V

Environment and Temperature

Halogen Free	No
Temperature Rating	90°C