



SKU: 45410-B10

UPC:

Features & Benefits:

Description:ILSCON Disconnect Terminal, Conductor Range 14-16, Flag, Female, Non-Insulated, 3/16in Width, Pack of 10

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
End Connection	Female
Mounting Hole Type	NA
Number of Conductors	1
Tongue Type	Quick slide flag

Dimensions

Height (IN)	0
Height BX (IN)	2
Length (IN)	0.49
Length (mm)	12.446
Maximum Wire Insulation Diameter (IN)	NA
Thickness (IN)	0.016
Thickness (mm)	0.4064
Weight (LB)	0.076
Weight BX (LB)	0.907
Width (IN)	0.187
Width BX (IN)	6.1875
Width (mm)	4.7498

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation	None
Material	Copper

General

Bag Quantity	10
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366945129



Bolt and Screw Sizes

Mounting Bolt/Stud Size

NA

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line) 14 Sol - 16 Sol

Conductor Range CU Stranded (Primary, run, main, line) 14 Str - 16 Str

Testing Standards

Prop65 Compliance

This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

UL Control Number

NA

UL File Number

NA

Color

Color

Silver