



SKU: ATAU-2/0-14

UPC: 0783669992199

Features & Benefits:

Description: Aluminum Anti-Turn Mechanical Lug, Conductor Range 2/0-14, 2 Conductors, 1/4in Bolt Size, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Anti-Turn Key	Yes
Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	2
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	2

Dimensions

Dimension G (IN)	0.34
Dimension G (mm)	8.636
Drive Size Main	3/16
Drive Type Main	Internal Hex
Height (IN)	0.849
Height (mm)	21.5646
Length (IN)	1.468
Length (mm)	37.2872
Mounting Hole Diameter (IN)	0.281
Mounting Hole Diameter (mm)	7.1374
Tang Length (IN)	0.843
Tang Length (mm)	21.4122
Tang Thickness (IN)	0.187
Tang Thickness (mm)	4.7498
Tang Width (IN)	1.25
Tang Width (mm)	31.75
Weight (LB)	0.056
Width (IN)	1.25
Width (mm)	31.75

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum



Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/4
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	7/16
Wire Binding Torque	120

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 15
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366999219

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	2/0 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol
Wire Combinations	NA



Voltage

Voltage Rating

35 kV