

SKU: AU-0

UPC: 0783669000665

Features & Benefits:

Description:Aluminum Mechanical Lug, Conductor Range 1/0-14, 2 Ports, 1 Hole, 1/4in Bolt Size, Tin Plated, UL, CSA

Specs

Additional Class Attributes


Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	2
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	2

Dimensions

Dimension G (IN)	0.422
Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.794
Height BX (IN)	2.25
Height (mm)	20.1676
Length (IN)	1.469
Length (mm)	37.3126
Mounting Hole Diameter (IN)	0.272
Mounting Hole Diameter (mm)	6.9088
Mounting Hole Spacing (mm)	0
Tang Length (IN)	0.844
Tang Length (mm)	21.4376
Tang Thickness (IN)	0.187
Tang Thickness (mm)	4.7498
Tang Width (IN)	1.125
Tang Width (mm)	28.575
Weight (LB)	0.137
Weight BX (LB)	1.8816
Width (IN)	1.125
Width BX (IN)	5
Width (mm)	28.575

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Aluminum



Additional Technical Specifications

Stranded

Bolt and Screw Sizes

General

Testing Standards

Environment and Temperature

Color

Conductor Ranges

nVent ILSCO
4701 Creek Rd, Suite 110
CINCINNATI, OH 45227
513-533-6200
800-776-9775



Voltage

Voltage Rating

35 kV