



SKU: BGC-2T-DB

UPC: 0783669001211

Features & Benefits:

Description:Permaground Bronze Ground Clamp, Conductor Range 2-10, Pipe Sizes 1/2 to 1in, Ground Rod Sizes 1/2 to 1in, Rebar Sizes #3-#8, Perpendicular Lay-in, Direcy Bury

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Perpendicular

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	2 Sol - 10 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2 Str - 10 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Ground Rod Size	7/8
NPS/IPS Pipe Size	3/4
Rebar Size(s) Main	#6 (3/4)

Dimensions

Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	2.653
Height BX (IN)	2.75
Height (mm)	67.3862
Length (IN)	2.245
Length (mm)	57.023
Weight (LB)	0.31
Weight BX (LB)	7.7519
Width (IN)	0.668
Width BX (IN)	6
Width (mm)	16.9672

Material and Finish

Clamping Hardware Material	Silicon bronze
Conductor Material	Copper



Connector Finish	Bright Dip
Insulation	NA
Material	Bronze
Wire Binding Hardware Material	Silicon bronze

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Clamping Bolt Size	1/4-20
Clamping Bolt Size (mm)	36068
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA
Wire Binding Torque	10 - 12 AWG = 35

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-2
UPC Code	78366900121

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	8M24
UL / CULUS Specification	UL 467 Listed
UL File Number	E207816