



SKU: BGRC-58

UPC: 0783669009965

Features & Benefits:

Description:Permaground Bronze Ground Rod Clamp, Conductor Range 1/0-8, Ground Rod Size 5/8in, Direct Bury

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Parallel

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	NA
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Conductor Range Solid with Ground Rod	NA
Conductor Range Solid with Rebar	NA
Conductor Range Str with Ground Rod	1/0 Str - 8 Str
Conductor Range Str with Rebar	1/0 Str - 8 Str
Conductor Size with Ground Rod	3 Str
Conductor Size with Rebar	7 Str
Ground Rod Size	5/8
Rebar Size(s) Main	#5 (5/8)

Dimensions

Drive Size Main	1/2
Drive Type Main	External Hex
Height (IN)	1.616
Height BX (IN)	2.0625
Height (mm)	41.0464
Length (IN)	0.925
Length (mm)	23.495
Weight (LB)	0.13
Weight BX (LB)	4.47
Width (IN)	1.031
Width BX (IN)	5.062
Width (mm)	26.1874



Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Cast bronze

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-2
UPC Code	78366900996

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440