



SKU: CA5SP

UPC: 0783669022056

Features & Benefits:

Description: Aluminum Box-Type Mechanical Lug, Conductor Range 1/0-14 CU, 1/0-12 AL, 1 Hole, Square Boss, Tin Plated

Specs

Dimensions

Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.737
Height BX (IN)	2.25
Height (mm)	18.7198
Length (IN)	0.625
Length (mm)	15.875
Mounting Bolt/Stud Size (mm)	26212.8
Mounting Hole Spacing (mm)	0
Size of Boss (IN)	0.229
Size of Boss (mm)	5.8166
Weight (LB)	0.021
Weight BX (LB)	1.975
Width (IN)	0.564
Width BX (IN)	5
Width (mm)	14.3256

Additional Class Attributes

Anti-Turn Key	No
Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Tap
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1
Style of Boss	Square

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum



Additional Technical Specifications

Conductor Type

Stranded

Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10-32
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	7/16
Wire Binding Torque	10 - 14 AWG = 35

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366902205

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL / CULUS Specification	UL 486A/B Recognized
UL File Number	E6207

Environment and Temperature

Temperature Rating	75°C
--------------------	------

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	1/0 Str - 12 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1/0 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 12 Sol
Wire Combinations	NA

Voltage

Voltage Rating	35 kV
----------------	-------

