SKU: CCL-6-14

UPC: 0783669031126

Features & Benefits:

Description: Copper Compression Lug, Conductor Size 6, 1 Hole, 1/4in Bolt Size, Standard Barrel, Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Index Number	I-24
Mounting Hole Type	Thru
Number of Mounting Holes	1
Sight Window	Yes
Slotted	No
Tang End Shape	Round
Undrilled	No

Dimensions

Barrel Length (IN)	0.425
Barrel Length (mm)	10.795
Dimension G (IN)	0.235
Dimension G (mm)	5.969
Height (IN)	0.385
Height BX (IN)	2.25
Height (mm)	9.779
Inside Diameter (IN)	0.232
Inside Diameter (mm)	5.8928
Length (IN)	1.27
Length (mm)	32.258
Mounting Hole Diameter (IN)	0.276
Mounting Hole Diameter (mm)	7.0104
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.325
Outside Diameter (mm)	8.255
Tang Length (IN)	0.55
Tang Length (mm)	13.97
Tang Thickness (IN)	0.08
Tang Thickness (mm)	2.032
Tang Width (IN)	0.445
Tang Width (mm)	11.303
Weight (LB)	0.012
Weight BX (LB)	1.024

Width (IN)	0.445
Width BX (IN)	4.375
Width (mm)	11.303

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	6 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	NA
Flex Conductor Range	6 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Flex

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366903112

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/4

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	No
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C

Color

Color	Silver
Color Code	Blue

Voltage

Voltage Rating	35 kV