



SKU: CDT-308-8

UPC: 0783669946789

Features & Benefits:

Description:Permaground Copper Grounding H-Tap, Double Tab, Main Conductor Range 4/0-2/0, Tap Range 1/0-2

Specs

Additional Class Attributes

Barrel Marking	Hard
Fixing Type	NA
ILSCOs Die Index Number	NA
Installing Dies	D3

Dimensions

Height (IN)	0.906
Height BX (IN)	3.625
Length (IN)	1.406
Weight (LB)	0.188
Weight BX (LB)	4.954
Width (IN)	1.062
Width BX (IN)	6.375

Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	Yes
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366994678



Bolt and Screw Sizes

Mounting Bolt/Stud Size

NA

Testing Standards

CSA File Number

NA

Prop65 Compliance

This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

UL Control Number

8M24

UL / CULUS Specification

UL 467 Listed

UL File Number

E158587

Environment and Temperature

Temperature Rating

NA

Color

Color

Copper

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

NA

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

NA

Conductor Range CU Solid (Secondary, tap, load)

NA

Conductor Range CU Stranded (Primary, run, main, line)

4/0 Str - 2/0 Str

Conductor Range CU Stranded (Secondary, tap, load)

1/0 Str - 2 Str

Conductor Range AL Solid (Primary, run, main, line)

NA