



SKU: CGP4-2250

UPC: 0783669005417

Features & Benefits:

Description:Permaground Copper Grounding Plate, Conductor Range 250-2, 4 Holes, UL

Specs

Additional Class Attributes

Barrel Marking	Hard
ILSCOs Die Index Number	NA
Installing Dies	15G86R
Mounting Hole Tapped Size	1/2-13
Mounting Method	Bolted
Number of Mounting Holes	4

Dimensions

Height (IN)	4.0313
Height (mm)	102.39502
Mounting Hole Spacing (IN)	1-3/4
Width (IN)	3.125
Width (mm)	79.375

Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Insulation	NA
Material	Cast copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-3
UPC Code	78366900541



Bolt and Screw Sizes

Mounting Bolt/Stud Size

1/2-13

Testing Standards

CSA File Number	NA
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	8M24
UL / CULUS Specification	IEEE 837
UL File Number	E158587

Environment and Temperature

Temperature Rating

NA

Color

Color

Copper

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 2 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA