



SKU: CGRC-48

UPC: 0783669026962

Features & Benefits:

Description:Permaground Bronze Ground Rod Clamp, Conductor Range 2-10, Ground Rod Size 1/2in, Rebar Size #4, UL

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Parallel

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	NA
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Conductor Range Solid with Ground Rod	10 Sol
Conductor Range Solid with Rebar	10 Sol
Conductor Range Str with Ground Rod	2 Str - 10 Str
Conductor Range Str with Rebar	2 Str - 10 Str
Conductor Size with Ground Rod	10 Str
Conductor Size with Rebar	10 Sol
Ground Rod Size	1/2
Rebar Size(s) Main	#4 (1/2)

Dimensions

Drive Size Main	19/32
Drive Type Main	External Hex
Height (IN)	1.48
Height BX (IN)	3.75
Height (mm)	37.592
Length (IN)	0.781
Length (mm)	19.8374
Weight (LB)	0.107
Weight BX (LB)	11
Width (IN)	0.615
Width BX (IN)	6
Width (mm)	15.621



Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Cast bronze
Wire Binding Hardware Material	Stainless steel

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	3/8

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 100
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-2
UPC Code	78366902696

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440