

## TYPE HPI



**Fig. 1**



**Fig. 2**



**Fig. 3**



**Fig. 4**



**Fig. 5**



**Fig. 6**



**Fig. 7**



**Fig. 8**



**Fig. 9**

| Figure Number | Catalog Number | Description                         |
|---------------|----------------|-------------------------------------|
| Fig. 1        | HSO-5          | 5 ft. Non-conductive filled hose    |
| Fig. 1        | HSO-10         | 10 ft. Non-conductive filled hose   |
| Fig. 1        | HSO-15         | 15 ft. Non-conductive filled hose   |
| Fig. 1        | HSO-30         | 30 ft. Non-conductive filled hose   |
| Fig. 2        | HSA-5          | 5 ft. Armored filled hose           |
| Fig. 2        | HSA-10         | 10 ft. Armored filled hose          |
| Fig. 2        | HSA-15         | 15 ft. Armored filled hose          |
| Fig. 2        | HSA-30         | 30 ft. Armored filled hose          |
| Fig. 3        | CH-120V        | 120V Battery charger                |
| Fig. 4        | CH-12V         | 12V Battery charger                 |
| Fig. 5*       | BAT-1850       | 18V 5.0 Ah Milwaukee Li-ion battery |
| Fig. 6*       | BAT-1820       | 18V 2.0 Ah Milwaukee Li-ion battery |
| Fig. 7        | RCPMP-5        | 5 ft. Hand held remote pump cord    |
| -             | SHST           | Shoulder strap for pump             |
| -             | USB            | 6 ft. 2.0 Cable Type A to Mini-B    |
| Fig. 8        | QCA-M          | Male adapter                        |
| Fig. 9        | QCA-F          | Female adapter                      |

\* Milwaukee Battery has 3 year warranty