



SKU: CLNB-400-58-4

UPC: 0783669678758

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 400, 1 Hole, 5/8in Bolt Size, Long Barrel, No Sight Window, 45° Bent Tang, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Hard
Barrel Type	Long
Connecting Angle	45°
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Catalog Number	ILD-76
ILSCOs Die Index Number	I-76
Mounting Hole Type	Thru
Narrow Tang	Yes
Number of Mounting Holes	1
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	2.125
Barrel Length (mm)	53.975
Dimension G (IN)	0.671
Dimension G (mm)	17.0434
Height (IN)	2.774
Height BX (IN)	1.875
Height (mm)	70.4596
Inside Diameter (IN)	0.75
Inside Diameter (mm)	19.05
Length (IN)	3.63
Length (mm)	92.202
Mounting Hole Diameter (IN)	0.656
Mounting Hole Diameter (mm)	16.6624
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.937
Outside Diameter (mm)	23.7998
Strip Length (mm)	55.5625
Tang Length (IN)	1.437
Tang Length (mm)	36.4998
Tang Thickness (IN)	0.187
Tang Thickness (mm)	4.7498
Tang Width (IN)	1.365



Tang Width (mm)	34.671
Weight (LB)	0.331953742862961
Weight BX (LB)	2.9101
Width (IN)	1.365
Width BX (IN)	4.625
Width (mm)	34.671

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	400 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	400 kcmil - 4/0 Str
Flex Conductor Range	300 G,H,I,K,M 313.1 DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366967875

Bolt and Screw Sizes

Mounting Bolt/Stud Size	5/8
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------



Color

Color	Silver
Color Code	Blue

Voltage

Voltage Rating	35 kV
----------------	-------