



SKU: CLNB-700-12-134-4

UPC: 0783669682182

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 700, 2 Holes, 1/2in Bolt Size, 1-3/4in Hole Spacing, Long Barrel, No Sight Window, 45° Bent Tang, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Hard
Barrel Type	Long
Connecting Angle	45°
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Catalog Number	ILD-99
ILSCOs Die Index Number	I-99
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	2.687
Barrel Length (mm)	68.2498
Dimension G (IN)	0.546
Dimension G (mm)	13.8684
Height (IN)	3.555
Height BX (IN)	3.5
Height (mm)	90.297
Inside Diameter (IN)	0.991
Inside Diameter (mm)	25.1714
Length (IN)	5.819
Length (mm)	147.8026
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.562
Mounting Hole Diameter (mm)	14.2748
Mounting Hole Spacing (IN)	1.75
Mounting Hole Spacing (mm)	44.45
Outside Diameter (IN)	1.25
Outside Diameter (mm)	31.75
Strip Length (mm)	69.8373
Tang Length (IN)	3
Tang Length (mm)	76.2
Tang Thickness (IN)	0.259



Tang Thickness (mm)	6.5786
Tang Width (IN)	1.816
Tang Width (mm)	46.1264
Weight (LB)	0.955458931531392
Weight BX (LB)	6.1639
Width (IN)	1.816
Width BX (IN)	5.875
Width (mm)	46.1264

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	700 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	700 kcmil - 350 kcmil
Flex Conductor Range	500 G,H,I, K,M 535.3 DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366968218

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207



Environment and Temperature

Temperature Rating

90°C

Color

Color

Silver

Color Code

Pink

Voltage

Voltage Rating

35 kV