




SKU: CLND-500-38-134

UPC: 0783669645989

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 500, 2 Holes, 3/8in Bolt Size, 1-3/4in Hole Spacing, Long Barrel, No Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-87
ILSCOs Die Index Number	I-87
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	2.25
Barrel Length (mm)	57.15
Dimension G (IN)	0.414
Dimension G (mm)	10.5156
Height (IN)	1.097
Height BX (IN)	2
Height (mm)	27.8638
Inside Diameter (IN)	0.828
Inside Diameter (mm)	21.0312
Length (IN)	5.607
Length (mm)	142.4178
Mounting Hole Diameter (IN)	0.406
Mounting Hole Diameter (mm)	10.3124
Mounting Hole Spacing (IN)	1.75
Mounting Hole Spacing (mm)	44.45
Outside Diameter (IN)	1.052
Outside Diameter (mm)	26.7208
Strip Length (mm)	58.7248
Tang Length (IN)	2.625
Tang Length (mm)	66.675
Tang Thickness (IN)	0.234
Tang Thickness (mm)	5.9436



Tang Width (IN)	1.535
Tang Width (mm)	38.989
Weight (LB)	0.592309280146724
Weight BX (LB)	3.8516
Width (IN)	1.535
Width BX (IN)	6.1875
Width (mm)	38.989

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	500 kcmil - 250 kcmil
Flex Conductor Range	350 G,H,I,K,M 373.7 DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Flex
----------------	------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366964598

Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 467 Listed
UL File Number	E6207

Environment and Temperature

Color

Color

Silver

Color Code

Brown

Voltage

Voltage Rating

35 kV