SKU: CLNF-1111-12-134

UPC: 0783669651522

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 1111, 2 Holes, 1/2in Bolt Size, 1-3/4in Hole Spacing, Long Barrel, No Sight Window, Flared End, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	Yes
ILSCOs Die Index Number	NA
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	2.998
Barrel Length (mm)	76.1492
Dimension G (IN)	0.625
Dimension G (mm)	15.875
Height (IN)	1.99
Height BX (IN)	2.75
Height (mm)	50.546
Inside Diameter (IN)	1.458
Inside Diameter (mm)	37.0332
Length (IN)	6.365
Length (mm)	161.671
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.563
Mounting Hole Diameter (mm)	14.3002
Mounting Hole Spacing (IN)	1.75
Mounting Hole Spacing (mm)	44.45
Outside Diameter (IN)	1.75
Outside Diameter (mm)	44.45
Strip Length (mm)	85.7377
Tang Length (IN)	3
Tang Length (mm)	76.2
Tang Thickness (IN)	0.29
Tang Thickness (mm)	7.366

Tang Width (IN)	2.6
Tang Width (mm)	66.04
Weight (LB)	1.898
Weight BX (LB)	9.7383
Width (IN)	2.6
Width BX (IN)	6
Width (mm)	66.04

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1111 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	NA
Flex Conductor Range	NA

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 5
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366965152

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	No
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C

Color

Color	Silver
Color Code	White

Voltage

Voltage Rating	35 kV