



SKU: CLNF-250-12

UPC: 0783669651294

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 250, 1 Hole, 1/2in Bolt Size, Long Barrel, No Sight Window, Flared End, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	Yes
ILSCOs Die Catalog Number	ILD-62
ILSCOs Die Index Number	I-62
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	1
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	1.95
Barrel Length (mm)	49.53
Dimension G (IN)	0.563
Dimension G (mm)	14.3002
Height (IN)	0.805
Height BX (IN)	2.25
Height (mm)	20.447
Inside Diameter (IN)	0.594
Inside Diameter (mm)	15.0876
Length (IN)	3.27
Length (mm)	83.058
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.531
Mounting Hole Diameter (mm)	13.4874
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.75
Outside Diameter (mm)	19.05
Strip Length (mm)	55.5625
Tang Length (IN)	1.125
Tang Length (mm)	28.575
Tang Thickness (IN)	0.156
Tang Thickness (mm)	3.9624



Tang Width (IN)	1.094
Tang Width (mm)	27.7876
Weight (LB)	0.221
Weight BX (LB)	3.113
Width (IN)	1.094
Width BX (IN)	5
Width (mm)	27.7876

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	250 kcmil - 1/0 Str
Flex Conductor Range	4/0 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366965129

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	No
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Color

Color

Silver

Color Code

Yellow

Voltage

Voltage Rating

35 kV