



SKU: CLNF-350-58

UPC: 0783669651331

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 350, 1 Hole, 5/8in Bolt Size, Long Barrel, No Sight Window, Flared End, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	Yes
ILSCOs Die Catalog Number	ILD-71
ILSCOs Die Index Number	I-71
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	1
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	2.34
Barrel Length (mm)	59.436
Dimension G (IN)	0.563
Dimension G (mm)	14.3002
Height (IN)	0.971
Height BX (IN)	2.25
Height (mm)	24.6634
Inside Diameter (IN)	0.703
Inside Diameter (mm)	17.8562
Length (IN)	3.66
Length (mm)	92.964
Mounting Hole Diameter (IN)	0.688
Mounting Hole Diameter (mm)	17.4752
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.892
Outside Diameter (mm)	22.6568
Strip Length (mm)	66.6877
Tang Length (IN)	1.125
Tang Length (mm)	28.575
Tang Thickness (IN)	0.188
Tang Thickness (mm)	4.7752
Tang Width (IN)	1.28



Tang Width (mm)	32.512
Weight (LB)	0.266456913312595
Weight BX (LB)	2.7215
Width (IN)	1.28
Width BX (IN)	5
Width (mm)	32.512

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	350 kcmil - 3/0 Str
Flex Conductor Range	250 I,K,M 262.2 DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Flex
----------------	------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 5
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366965133

Bolt and Screw Sizes

Mounting Bolt/Stud Size	5/8
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	No
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------



Color

Color	Silver
Color Code	Red

Voltage

Voltage Rating	35 kV
----------------	-------