



SKU: CLNF-400-12-134

UPC: 0783669651348

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 400, 2 Holes, 1/2in Bolt Size, 1-3/4in Hole Spacing, Long Barrel, No Sight Window, Flared End, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	Yes
ILSCOs Die Catalog Number	ILD-76
ILSCOs Die Index Number	I-76
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	2.373
Barrel Length (mm)	60.2742
Dimension G (IN)	0.625
Dimension G (mm)	15.875
Height (IN)	1.018
Height BX (IN)	2
Height (mm)	25.8572
Inside Diameter (IN)	0.75
Inside Diameter (mm)	19.05
Length (IN)	5.66
Length (mm)	143.764
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.563
Mounting Hole Diameter (mm)	14.3002
Mounting Hole Spacing (IN)	1.75
Mounting Hole Spacing (mm)	44.45
Outside Diameter (IN)	0.938
Outside Diameter (mm)	23.8252
Strip Length (mm)	69.8627
Tang Length (IN)	3
Tang Length (mm)	76.2
Tang Thickness (IN)	0.188



Tang Thickness (mm)	4.7752
Tang Width (IN)	1.375
Tang Width (mm)	34.925
Weight (LB)	0.608
Weight BX (LB)	3.1871
Width (IN)	1.375
Width BX (IN)	6.188
Width (mm)	34.925

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	400 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	400 kcmil - 4/0 Str
Flex Conductor Range	300 G,H,I,K,M 313.1 DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 5
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366965134

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	No
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207



Environment and Temperature

Temperature Rating

90°C

Color

Color

Silver

Color Code

Blue

Voltage

Voltage Rating

35 kV