



SKU: CLNF-700-12-134

UPC: 0783669651423

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 700, 2 Holes, 1/2in Bolt Size, 1-3/4in Hole Spacing, Long Barrel, No Sight Window, Flared End, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	Yes
ILSCOs Die Catalog Number	ILD-99
ILSCOs Die Index Number	I-99
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	2.64
Barrel Length (mm)	67.056
Dimension G (IN)	0.625
Dimension G (mm)	15.875
Height (IN)	1.43
Height BX (IN)	2
Height (mm)	36.322
Inside Diameter (IN)	0.991
Inside Diameter (mm)	25.1714
Length (IN)	5.835
Length (mm)	148.209
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.563
Mounting Hole Diameter (mm)	14.3002
Mounting Hole Spacing (IN)	1.75
Mounting Hole Spacing (mm)	44.45
Outside Diameter (IN)	1.25
Outside Diameter (mm)	31.75
Strip Length (mm)	73.0377
Tang Length (IN)	3
Tang Length (mm)	76.2
Tang Thickness (IN)	0.265



Tang Thickness (mm)	6.731
Tang Width (IN)	1.844
Tang Width (mm)	46.8376
Weight (LB)	1.124
Weight BX (LB)	5.77
Width (IN)	1.844
Width BX (IN)	6.188
Width (mm)	46.8376

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	700 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	700 kcmil - 350 kcmil
Flex Conductor Range	500 G,H,I, K,M 535.3 DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 5
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366965142

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	No
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207



Environment and Temperature

Temperature Rating

90°C

Color

Color

Silver

Color Code

Pink

Voltage

Voltage Rating

35 kV