SKU: CLNS-4-12

UPC: 0783669630428

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 4, 1 Hole, 1/2in Bolt Size, Long Barrel, No Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Catalog Number	ILD-29
ILSCOs Die Index Number	I-29
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	1
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	1.125
Barrel Length (mm)	28.575
Dimension G (IN)	0.546
Dimension G (mm)	13.8684
Height (IN)	0.373
Height BX (IN)	2.25
Height (mm)	9.4742
Inside Diameter (IN)	0.25
Inside Diameter (mm)	6.35
Length (IN)	2.609
Length (mm)	66.2686
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.562
Mounting Hole Diameter (mm)	14.2748
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.343
Outside Diameter (mm)	8.7122
Strip Length (IN)	1.187
Strip Length (mm)	30.1498
Tang Length (IN)	1.25
Tang Length (mm)	31.75
Tang Thickness (IN)	0.093

Tang Thickness (mm)	2.3622
Tang Width (IN)	0.755
Tang Width (mm)	19.177
Weight (LB)	0.0396218011548019
Weight BX (LB)	2.6722
Width (IN)	0.755
Width BX (IN)	5
Width (mm)	19.177

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	4 Sol
Conductor Range CU Stranded (Primary, run, main, line)	4 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	4 Str - 6 Str
Flex Conductor Range	NA

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Solid

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366963042

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 467 Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C

Color

Color	Silver
Color Code	Gray

Voltage

Voltage Rating	35 kV