




SKU: CLWD-1000-58-112

UPC: 0783669651157

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 1000, 2 Holes, 5/8in Bolt Size, 1-1/2in Hole Spacing, Long Barrel, Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-125
ILSCOs Die Index Number	I-125
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	Yes
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	3
Barrel Length (mm)	76.2
Dimension G (IN)	0.671
Dimension G (mm)	17.0434
Height (IN)	1.55
Height BX (IN)	2
Height (mm)	39.37
Inside Diameter (IN)	1.172
Inside Diameter (mm)	29.7688
Length (IN)	7.025
Length (mm)	178.435
Mounting Hole Diameter (IN)	0.656
Mounting Hole Diameter (mm)	16.6624
Mounting Hole Spacing (IN)	1.5
Mounting Hole Spacing (mm)	38.1
Outside Diameter (IN)	1.5
Outside Diameter (mm)	38.1
Strip Length (mm)	77.7748
Tang Length (IN)	3
Tang Length (mm)	76.2
Tang Thickness (IN)	0.328
Tang Thickness (mm)	8.3312



Tang Width (IN)	2.169
Tang Width (mm)	55.0926
Weight (LB)	1.45376357950055
Weight BX (LB)	4.7398
Width (IN)	2.169
Width BX (IN)	6.1875
Width (mm)	55.0926

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1000 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	1000 kcmil - 750 kcmil
Flex Conductor Range	750 G,H,I 777.7 DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366965115

Bolt and Screw Sizes

Mounting Bolt/Stud Size	5/8
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Color

Color	Silver
Color Code	White

Voltage

Voltage Rating	35 kV
----------------	-------