



SKU: CLWD-3/0-14-34

UPC: 0783669638790

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 3/0, 2 Holes, 1/4in Bolt Size, 3/4in Hole Spacing, Long Barrel, Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-50
ILSCOs Die Index Number	I-50
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	Yes
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	1.5
Barrel Length (mm)	38.1
Dimension G (IN)	0.321
Dimension G (mm)	8.1534
Height (IN)	0.649
Height BX (IN)	2.25
Height (mm)	16.4846
Inside Diameter (IN)	0.484
Inside Diameter (mm)	12.2936
Length (IN)	3.376
Length (mm)	85.7504
Mounting Hole Diameter (IN)	0.281
Mounting Hole Diameter (mm)	7.1374
Mounting Hole Spacing (IN)	0.75
Mounting Hole Spacing (mm)	19.05
Outside Diameter (IN)	0.609
Outside Diameter (mm)	15.4686
Strip Length (mm)	39.6748
Tang Length (IN)	1.437
Tang Length (mm)	36.4998
Tang Thickness (IN)	0.125
Tang Thickness (mm)	3.175



Tang Width (IN)	0.885
Tang Width (mm)	22.479
Weight (LB)	0.110233788025107
Weight BX (LB)	2.042
Width (IN)	0.885
Width BX (IN)	5
Width (mm)	22.479

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	3/0 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	3/0 Str - 2 Str
Flex Conductor Range	2/0 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366963879

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/4
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

90°C

Color

Color

Silver

Color Code

Orange

Voltage

Voltage Rating

35 kV