



SKU: CLWD-8-14-34

UPC: 0783669628111

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 8, 2 Holes, 1/4in Bolt Size, 3/4in Hole Spacing, Long Barrel, Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-21
ILSCOs Die Index Number	I-21
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	Yes
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	0.812
Barrel Length (mm)	20.6248
Dimension G (IN)	0.321
Dimension G (mm)	8.1534
Height (IN)	0.303
Height BX (IN)	2.25
Height (mm)	7.6962
Inside Diameter (IN)	0.179
Inside Diameter (mm)	4.5466
Length (IN)	2.444
Length (mm)	62.0776
Mounting Hole Diameter (IN)	0.281
Mounting Hole Diameter (mm)	7.1374
Mounting Hole Spacing (IN)	0.75
Mounting Hole Spacing (mm)	19.05
Outside Diameter (IN)	0.273
Outside Diameter (mm)	6.9342
Strip Length (mm)	22.1996
Tang Length (IN)	1.437
Tang Length (mm)	36.4998
Tang Thickness (IN)	0.094
Tang Thickness (mm)	2.3876



Tang Width (IN)	0.491
Tang Width (mm)	12.4714
Weight (LB)	0.0276573821666059
Weight BX (LB)	2.1549
Width (IN)	0.491
Width BX (IN)	5
Width (mm)	12.4714

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	8 Sol
Conductor Range CU Stranded (Primary, run, main, line)	8 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	NA
Flex Conductor Range	8 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366962811

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/4
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Color

Color	Silver
Color Code	Red

Voltage

Voltage Rating	35 kV
----------------	-------