

SKU: CLWS-6-10

UPC: 0783669628913

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 6, 1 Hole, #10 Bolt Size, Long Barrel, Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-24
ILSCOs Die Index Number	I-24
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	1
Sight Window	Yes
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	1.125
Barrel Length (mm)	28.575
Dimension G (IN)	0.258
Dimension G (mm)	6.5532
Height (IN)	0.343
Height BX (IN)	2.25
Height (mm)	8.7122
Inside Diameter (IN)	0.225
Inside Diameter (mm)	5.715
Length (IN)	1.882
Length (mm)	47.8028
Mounting Bolt/Stud Size (mm)	254
Mounting Hole Diameter (IN)	0.219
Mounting Hole Diameter (mm)	5.5626
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.313
Outside Diameter (mm)	7.9502
Strip Length (mm)	30.1498
Tang Length (IN)	0.562
Tang Length (mm)	14.2748
Tang Thickness (IN)	0.087
Tang Thickness (mm)	2.2098

Tang Width (IN)	0.44
Tang Width (mm)	11.176
Weight (LB)	0.0211750723409061
Weight BX (LB)	1.935
Width (IN)	0.44
Width BX (IN)	5
Width (mm)	11.176

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	6 Sol
Conductor Range CU Stranded (Primary, run, main, line)	6 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	NA
Flex Conductor Range	6 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Solid

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366962891

Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C

Color

Color	Silver
Color Code	Blue

Voltage

Voltage Rating	35 kV