




SKU: CO5SP

UPC: 0783669027556

Features & Benefits:

Description: Copper Box-Type Mechanical Lug, Conductor Range 1/0-6, 1 Hole, Square Boss

Specs

Dimensions

Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.685
Height BX (IN)	2.25
Height (mm)	17.399
Length (IN)	0.615
Length (mm)	15.621
Mounting Bolt/Stud Size (mm)	26212.8
Mounting Hole Diameter (IN)	0.164
Mounting Hole Diameter (mm)	4.1656
Mounting Hole Spacing (IN)	0
Mounting Hole Spacing (mm)	0
Size of Boss (IN)	0.229
Size of Boss (mm)	5.8166
Weight (LB)	0.046
Weight BX (LB)	3.22
Width (IN)	0.56
Width BX (IN)	5
Width (mm)	14.224

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Tap
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1
Style of Boss	Square

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper
Wire Binding Hardware Finish	Zinc Clear Trivalent Chromate
Wire Binding Hardware Material	Steel



Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10-32
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	7/16
Wire Binding Torque	10 - 14 AWG = 35

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366902755

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL / CULUS Specification	UL 486A/B Recognized
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Copper
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1/0 Str - 6 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Wire Combinations	NA

Voltage



35 kV