



SKU: CST-302

UPC: 0783669005493

Features & Benefits:

Description: Permaground Copper Grounding H-Tap, Single Tab, Main Conductor Range 2-4 Sol, Tap Range 2-6 Sol

Specs

Additional Class Attributes

Barrel Marking	Hard
Fixing Type	NA
ILSCOs Die Index Number	NA
Installing Dies	KK

Dimensions

Height (IN)	0
Height BX (IN)	2.25
Length (IN)	0
Weight (LB)	0.121
Weight BX (LB)	3.115
Width (IN)	0
Width BX (IN)	5

Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	Yes
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366900549



Bolt and Screw Sizes

Mounting Bolt/Stud Size

NA

Testing Standards

CSA File Number

NA

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -
www.P65warnings.ca.gov

UL Control Number

8M24

UL / CULUS Specification

UL 486A/B Listed

UL File Number

E158587

Environment and Temperature

Temperature Rating

NA

Color

Color

Copper

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

NA

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

2 Sol - 4 Sol

Conductor Range CU Solid (Secondary, tap, load)

2 Sol - 6 Sol

Conductor Range CU Stranded (Primary, run, main, line)

4 Str

Conductor Range CU Stranded (Secondary, tap, load)

4 Str - 6 Str