



SKU: CSWD-10-14-58

UPC: 0783669691818

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 10, 2 Holes, 1/4in Bolt Size, 5/8in Hole Spacing, Standard Barrel, Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Index Number	NA
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	Yes
Slotted	No
Tang End Shape	Slightly Round
Undrilled	No

Dimensions

Barrel Length (IN)	0.39
Barrel Length (mm)	9.906
Dimension G (IN)	0.29
Dimension G (mm)	7.366
Height (IN)	0.261
Height BX (IN)	2.25
Height (mm)	6.6294
Inside Diameter (IN)	0.149
Inside Diameter (mm)	3.7846
Length (IN)	1.76
Length (mm)	44.704
Mounting Hole Diameter (IN)	0.281
Mounting Hole Diameter (mm)	7.1374
Mounting Hole Spacing (IN)	0.63
Mounting Hole Spacing (mm)	16.002
Outside Diameter (IN)	0.237
Outside Diameter (mm)	6.0198
Strip Length (mm)	11.4935
Tang Length (IN)	1.25
Tang Length (mm)	31.75
Tang Thickness (IN)	0.06
Tang Thickness (mm)	1.524
Tang Width (IN)	0.42



Tang Width (mm)	10.668
Weight (LB)	0.0113886000662372
Weight BX (LB)	0.86
Width (IN)	0.42
Width BX (IN)	5
Width (mm)	10.668

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol
Conductor Range CU Stranded (Primary, run, main, line)	10 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	10 Str - 14 Str /10 Sol - 12 Sol
Flex Conductor Range	NA

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366969181

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/4
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 467 Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------



Color

Color	Silver
Color Code	NA

Voltage

Voltage Rating	35 kV
----------------	-------