



SKU: CSWD-2/0-516-1

UPC: 0783669637694

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 2/0, 2 Holes, 5/16in Bolt Size, 1in Hole Spacing, Standard Barrel, Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-45
ILSCOs Die Index Number	I-45
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	Yes
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	0.75
Barrel Length (mm)	19.05
Dimension G (IN)	0.352
Dimension G (mm)	8.9408
Height (IN)	0.597
Height BX (IN)	2.25
Height (mm)	15.1638
Inside Diameter (IN)	0.437
Inside Diameter (mm)	11.0998
Length (IN)	3.083
Length (mm)	78.3082
Mounting Hole Diameter (IN)	0.343
Mounting Hole Diameter (mm)	8.7122
Mounting Hole Spacing (IN)	1
Mounting Hole Spacing (mm)	25.4
Outside Diameter (IN)	0.562
Outside Diameter (mm)	14.2748
Strip Length (mm)	20.6248
Tang Length (IN)	1.937
Tang Length (mm)	49.1998
Tang Thickness (IN)	0.125
Tang Thickness (mm)	3.175



Tang Width (IN)	0.811
Tang Width (mm)	20.5994
Weight (LB)	0.0886653833545555
Weight BX (LB)	1.836
Width (IN)	0.811
Width BX (IN)	5
Width (mm)	20.5994

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	2/0 Str - 4 Str
Flex Conductor Range	1/0 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Flex
----------------	------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366963769

Bolt and Screw Sizes

Mounting Bolt/Stud Size	5/16
-------------------------	------

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 467 Listed
UL File Number	E6207

Environment and Temperature

Color

Color	Silver
Color Code	Black

Voltage

Voltage Rating	35 kV
----------------	-------