

SKU: CSWD-3-12-134

UPC: 0783669632897

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 3, 2 Holes, 1/2in Bolt Size, 1-3/4in Hole Spacing, Standard Barrel, Sight Window, Tin Plated, UL, CSA



Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-29
ILSCOs Die Index Number	I-29
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	Yes
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	0.625
Barrel Length (mm)	15.875
Dimension G (IN)	0.546
Dimension G (mm)	13.8684
Height (IN)	0.405
Height BX (IN)	2.25
Height (mm)	10.287
Inside Diameter (IN)	0.275
Inside Diameter (mm)	6.985
Length (IN)	3.88
Length (mm)	98.552
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.562
Mounting Hole Diameter (mm)	14.2748
Mounting Hole Spacing (IN)	1.75
Mounting Hole Spacing (mm)	44.45
Outside Diameter (IN)	0.375
Outside Diameter (mm)	9.525
Strip Length (mm)	17.4498
Tang Length (IN)	3
Tang Length (mm)	76.2
Tang Thickness (IN)	0.1



Tang Thickness (mm)	2.54
Tang Width (IN)	0.749
Tang Width (mm)	19.0246
Weight (LB)	0.0692959766602651
Weight BX (LB)	2.5904
Width (IN)	0.749
Width BX (IN)	5
Width (mm)	19.0246

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	3 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	3 Str - 6 Str
Flex Conductor Range	4 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366963289

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 467 Listed
UL File Number	E6207



Environment and Temperature

Temperature Rating

90°C

Color

Color

Silver

Color Code

White

Voltage

Voltage Rating

35 kV