

SKU: CSWD-3-14-58

UPC: 0783669632170

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 3, 2 Holes, 1/4in Bolt Size, 5/8in Hole Spacing, Standard Barrel, Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-29
ILSCOs Die Index Number	I-29
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	Yes
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	0.625
Barrel Length (mm)	15.875
Dimension G (IN)	0.321
Dimension G (mm)	8.1534
Height (IN)	0.405
Height BX (IN)	2.25
Height (mm)	10.287
Inside Diameter (IN)	0.275
Inside Diameter (mm)	6.985
Length (IN)	2.317
Length (mm)	58.8518
Mounting Hole Diameter (IN)	0.281
Mounting Hole Diameter (mm)	7.1374
Mounting Hole Spacing (IN)	0.625
Mounting Hole Spacing (mm)	15.875
Outside Diameter (IN)	0.375
Outside Diameter (mm)	9.525
Strip Length (mm)	17.4498
Tang Length (IN)	1.437
Tang Length (mm)	36.4998
Tang Thickness (IN)	0.1
Tang Thickness (mm)	2.54

Tang Width (IN)	0.532
Tang Width (mm)	13.5128
Weight (LB)	0.0336191567177902
Weight BX (LB)	1.8025
Width (IN)	0.532
Width BX (IN)	5
Width (mm)	13.5128

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	3 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	3 Str - 6 Str
Flex Conductor Range	4 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366963217

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/4

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C

Color

Color	Silver
Color Code	White

Voltage

Voltage Rating	35 kV