



**SKU:** D167-8

**UPC:** 0783669161212



**Features & Benefits:**

**Description:** Copper Neutral Bar, Conductor Range 4-14 Main, 6-14 Tap, 9 Ports

## Specs

### Additional Class Attributes

|                          |            |
|--------------------------|------------|
| Connection               | Mechanical |
| Mounting Hole Type       | Thru       |
| Number of Conductors     | 1          |
| Number of Mounting Holes | 2          |
| Number of Poles          | 1          |
| Number of Ports Tap      | 8          |

### Dimensions

|                              |                    |
|------------------------------|--------------------|
| Dimension G (IN)             | 0.984              |
| Dimension G (mm)             | 24.9936            |
| Drive Size Main              | NA                 |
| Drive Type Main              | Slotted            |
| Height (IN)                  | 0.482              |
| Height BX (IN)               | 2.25               |
| Height (mm)                  | 12.2428            |
| Length (IN)                  | 4.344              |
| Mounting Bolt/Stud Size (mm) | 254                |
| Mounting Hole Diameter (IN)  | 0.203              |
| Mounting Hole Diameter (mm)  | 5.1562             |
| Mounting Hole Position (IN)  | 4 & 9              |
| Mounting Hole Spacing (IN)   | 1.984              |
| Mounting Hole Spacing (mm)   | 50.3936            |
| Weight (LB)                  | 0.0942327988804427 |
| Weight BX (LB)               | 3.2637             |
| Width (IN)                   | 0.342              |
| Width BX (IN)                | 5                  |
| Width (mm)                   | 8.6868             |

### Material and Finish

|                                |                               |
|--------------------------------|-------------------------------|
| Conductor Material             | Copper                        |
| Connector Finish               | NA                            |
| Insulation                     | NA                            |
| Material                       | Copper                        |
| Wire Binding Hardware Finish   | Zinc Clear Trivalent Chromate |
| Wire Binding Hardware Material | Steel                         |



## Additional Technical Specifications

Conductor Type

Solid

### Bolt and Screw Sizes

|                                        |            |
|----------------------------------------|------------|
| Mounting Bolt/Stud Size                | #10        |
| Number of Wire Binding Screws per Port | 1          |
| Wire Binding Screw Size                | 1/4        |
| Wire Binding Torque                    | 2 AWG = 40 |

### General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 1               |
| Carton Quantity Description | STD PACK QTY 20 |
| Dual Rated                  | No              |
| NEMA Code                   | 0-000-1         |
| UPC Code                    | 78366916121     |

### Testing Standards

|                          |                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------|
| CSA File Number          | LR-29601                                                                                                            |
| CSA Standard             | C22.2 No. 65-03                                                                                                     |
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| ROHS Indicator           | IND                                                                                                                 |
| UL Control Number        | NA                                                                                                                  |
| UL / CULUS Specification | UL 486A/B Recognized                                                                                                |
| UL File Number           | E6207                                                                                                               |

### Color

Color

Copper

### Conductor Ranges

|                                                        |                 |
|--------------------------------------------------------|-----------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA              |
| Conductor Range AL Stranded (Primary, run, main, line) | NA              |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA              |
| Conductor Range CU Solid (Primary, run, main, line)    | 10 Sol - 14 Sol |
| Conductor Range CU Solid (Secondary, tap, load)        | 10 Sol - 14 Sol |
| Conductor Range CU Stranded (Primary, run, main, line) | 4 Str - 14 Str  |
| Conductor Range CU Stranded (Secondary, tap, load)     | 6 Str - 14 Str  |
| Conductor Range AL Solid (Primary, run, main, line)    | NA              |