



SKU: DBK-2

UPC: 0783669232134



Features & Benefits:

Description: Direct Burial Splice Kit, Dual Rated, Conductor Range 2-8, Includes (1) SPA-2 Splice and (2) Pieces of Heat Shrink, UL, CSA

Specs

Additional Class Attributes

Includes	(1) SPA-2, (2) Pieces of heat shrink
Number of Conductors	2

Dimensions

Height (IN)	1.5
Height BX (IN)	3.75
Height (mm)	38.1
Length (IN)	14
Length (mm)	355.6
Weight (LB)	0.0559682530345732
Weight BX (LB)	3.1613
Width (IN)	4
Width BX (IN)	6.5
Width (mm)	101.6

Material and Finish

Conductor Material	Aluminum
Material	Polyolefin
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	Yes
NEMA Code	S-569-1
UPC Code	78366923213



Testing Standards

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -
www.P65warnings.ca.gov

UL Control Number

88X4

UL / CULUS Specification

UL 486D Listed

UL File Number

E125087

Environment and Temperature

Temperature Rating

90°C

Color

Color

Silver

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

2 Str - 8 Str

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

NA

Conductor Range CU Solid (Secondary, tap, load)

NA

Conductor Range CU Stranded (Primary, run, main, line)

2 Str - 8 Str

Conductor Range CU Stranded (Secondary, tap, load)

NA

Conductor Range AL Solid (Primary, run, main, line)

NA

Voltage

Voltage Rating

600 V