



**SKU:** ECTD-3-350-SR

**UPC:** 0783669025279

**Features & Benefits:**

**Description:** ClearTap Insulated Aluminum Multi-Tap Connector, Conductor Range 350-6, 3 Ports, Dual Sided Entry, Tin Plated, UL, CSA, SR Rated

## Specs

### Additional Class Attributes

|                            |            |
|----------------------------|------------|
| Connection                 | Mechanical |
| Contains DE-OX®            | Yes        |
| Number of Conductors       | 3          |
| Number of Poles            | 1          |
| Number of Ports / Wireways | 3          |
| Number of Usable Ports     | 3          |

### Material and Finish

|                                |           |
|--------------------------------|-----------|
| Connector Finish               | Tin       |
| Insulation                     | Plastisol |
| Material                       | Aluminum  |
| Wire Binding Hardware Finish   | Tin       |
| Wire Binding Hardware Material | Aluminum  |

### Dimensions

|                 |              |
|-----------------|--------------|
| Drive Size Main | 5/16         |
| Drive Type Main | Internal Hex |

### Additional Technical Specifications

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

### Bolt and Screw Sizes

|                                        |       |
|----------------------------------------|-------|
| Number of Wire Binding Screws per Port | 1     |
| Wire Binding Screw Size                | 11/16 |
| Wire Binding Torque                    | 275   |

### Conductor Ranges

|                                                        |                   |
|--------------------------------------------------------|-------------------|
| Conductor Range AL Stranded (Primary, run, main, line) | 350 kcmil - 6 Str |
| Conductor Range CU Stranded (Primary, run, main, line) | 350 kcmil - 6 Str |



### General

|                             |                |
|-----------------------------|----------------|
| Carton Quantity Description | STD PACK QTY 4 |
| Dual Rated                  | Yes            |
| UPC Code                    | 78366902527    |

### Color

|       |       |
|-------|-------|
| Color | Clear |
|-------|-------|

### Voltage

|                |       |
|----------------|-------|
| Voltage Rating | 600 V |
|----------------|-------|

### Environment and Temperature

|                          |                                 |
|--------------------------|---------------------------------|
| Environmental Conditions | Cold temperature rated to -45°C |
| Flammability Rating      | Insulation rated per UL 94      |
| Temperature Rating       | 90°C                            |