



SKU: ECTS-2-3/0

UPC: 0783669019681

Features & Benefits:

Description: ClearTap Insulated Aluminum Multi-Tap Connector, Conductor Range 3/0-6, 2 Ports, Single Sided Entry, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	2
Number of Poles	1
Number of Ports / Wireways	2
Number of Usable Ports	2
Number of Usable Taps	2
Replacement Part(s)	PLUG-3/0

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation Material	Plastisol
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Dimensions

Drive Size Main	1/4
Drive Type Main	Internal Hex

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	1/2
Wire Binding Torque	200

General

Bag Quantity	0
--------------	---



Carton Quantity Description	STD PACK QTY 12
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366901968

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	3/0 Str - 6 Str
Conductor Range CU Stranded (Primary, run, main, line)	3/0 Str - 6 Str

Voltage

Voltage Rating	600 V
----------------	-------

Color

Cap Color Main	Black
Cap Color Tap	Black
Color	Clear

Environment and Temperature

Environmental Conditions	Cold temperature rated to -45°C
Flammability Rating	Insulation rated per UL 94
Temperature Rating	90°C