



SKU: ELT-5

UPC: 0783669257380

Features & Benefits:

Description:Permaground Copper Grounding E Crimp, Main Conductor Range 250-3/0, Main Rebar Size #4, Tap Range 2/0-6 Sol, Tap Rebar Size #3, UL, CSA

Specs

Additional Class Attributes

Fixing Type	NA
ILSCOs Die Index Number	997

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	2/0 Sol - 6 Sol
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 3/0 Str
Conductor Range CU Stranded (Secondary, tap, load)	2/0 Str - 6 Str
Ground Rod Size	1/2
Rebar Size(s) Main	#4 (1/2)
Rebar Size(s) Secondary	#3 (3/8)

Dimensions

Height (IN)	0.75
Height BX (IN)	2.25
Length (IN)	1.968
Weight (LB)	0.221
Weight BX (LB)	3.3224
Width (IN)	0.922
Width BX (IN)	4.375

Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
--------------	---



Carton Quantity Description	STD PACK QTY 6
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-3
UPC Code	78366925738

Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL / CULUS Specification	UL 467 Listed

Environment and Temperature

Temperature Rating	NA
--------------------	----

Color

Color	Copper
-------	--------