



SKU: ELT-8

UPC: 0783669257441

Features & Benefits:

Description:Permaground Copper Grounding E Crimp, Main Conductor Range 500-300, Main Rebar Size #5-#6, Tap Range 500-300, Tap Rebar Size #5-#6, UL, CSA

Specs

Additional Class Attributes

Fixing Type	NA
ILSCOs Die Index Number	1011

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 300 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	500 kcmil - 300 kcmil
Ground Rod Size	5/8
Rebar Size(s) Main	#6 (3/4)
Rebar Size(s) Secondary	#5 (5/8)

Dimensions

Height (IN)	2.818
Height BX (IN)	2
Height (mm)	71.5772
Length (IN)	1.328
Length (mm)	33.7312
Weight (LB)	0.482
Weight BX (LB)	2.962
Width (IN)	0.875
Width BX (IN)	5
Width (mm)	22.225

Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------



General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-3
UPC Code	78366925744

Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL / CULUS Specification	UL 467 Listed

Environment and Temperature

Temperature Rating	NA
--------------------	----

Color

Color	Copper
-------	--------