



**SKU:** F2C-4-4

**UPC:** 0783669017830

**Features & Benefits:**

**Description:** Flex2Code™, Copper Pin Adaptor, Flex Conductor Range 4

## Specs

### Additional Class Attributes

|                         |             |
|-------------------------|-------------|
| Connecting Angle        | 180°        |
| Connection              | Compression |
| ILSCOs Die Index Number | I-29        |
| Replacement Part(s)     | PCC-2       |

### Conductor Ranges

|                          |                 |
|--------------------------|-----------------|
| Approximate Pin Size     | 4 AWG           |
| Expanded Conductor Range | 3 Str - 6 Str   |
| Flex Conductor Range     | 4 G,H,I,K,M,DLO |

### Material and Finish

|                  |                                |
|------------------|--------------------------------|
| Connector Finish | Tin                            |
| Insulation       | Supplied with insulating cover |
| Material         | Copper                         |

### General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 0               |
| Carton Quantity Description | STD PACK QTY 25 |
| NEMA Code                   | S-588-3         |
| UPC Code                    | 78366901783     |

### Testing Standards

|                          |                      |
|--------------------------|----------------------|
| UL Control Number        | 453G                 |
| UL / CULUS Specification | UL/cUL 486A/B Listed |
| UL File Number           | E34440               |

### Color

|            |       |
|------------|-------|
| Color Code | White |
|------------|-------|



## Voltage

Voltage Rating

600 V