



SKU: GBL-4DBTH-14

UPC: 0783669960273

Features & Benefits:

Description: Permaground Copper Lay-in Groud Lug, Conductor Size 4-14, 1/4 Bolt Size, Hex Head, Tin Plated

Specs

Additional Class Attributes

Connection	Mechanical
Mounting Hole Type	Thru
Mounting Kit Hardware Part #	GBL-MH3
Number of Conductors	1
Number of Mounting Holes	1
Number of Ports / Wireways	1
Wire Orientation	NA

Dimensions

Dimension G (IN)	0.21
Dimension G (mm)	5.334
Drive Size Main	7/16
Drive Type Main	External Hex
Height (IN)	0.965
Height BX (IN)	2.25
Height (mm)	24.511
Length (IN)	1.194
Length (mm)	30.3276
Mounting Hole Diameter (IN)	0.265
Mounting Hole Diameter (mm)	6.731
Tang Length (IN)	0.47
Tang Length (mm)	11.938
Tang Thickness (IN)	0.185
Tang Thickness (mm)	4.699
Tang Width (IN)	0.472
Tang Width (mm)	11.9888
Weight (LB)	0.0848683950294886
Weight BX (LB)	4.3
Width (IN)	0.472
Width BX (IN)	5
Width (mm)	11.9888

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper



Wire Binding Hardware Finish
Wire Binding Hardware Material

Nickel Strick, Zinc, Green Dye
Stainless steel

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/4
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	1/4
Wire Binding Torque	10 - 18 AWG = 20

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-2
UPC Code	78366996027

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	667P
UL / CULUS Specification	UL 2703 Listed
UL File Number	E34440

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA