



SKU: GBT-250

UPC: 0783669000726

Features & Benefits:

Description: Aluminum Intersystem Ground Tap, Dual Rated, Main Conductor Range 250-8, Tap Range 2-14, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Mounting Hole Type	NA
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Perpendicular

Dimensions

Height (IN)	1.587
Height BX (IN)	2.25
Height (mm)	40.3098
Length (IN)	2.25
Length (mm)	57.15
Weight (LB)	0.405
Weight BX (LB)	3.3301
Width (IN)	1.375
Width BX (IN)	5
Width (mm)	34.925

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Enclosure Material	NA
Insulation	NA
Material	Aluminum
Wire Binding Hardware Material	Stainless steel

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	Yes



Dual Rated	Yes
NEMA Code	S-573-2
UPC Code	78366900072

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	2 Sol - 14 Sol
Conductor Range AL Stranded (Primary, run, main, line)	250 kcmil - 8 Str
Conductor Range AL Stranded (Secondary, tap, load)	2 Str - 14 Str
Conductor Range CU Solid (Primary, run, main, line)	1/0 Sol - 8 Sol
Conductor Range CU Solid (Secondary, tap, load)	2 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 8 Str
Conductor Range CU Stranded (Secondary, tap, load)	2 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	1/0 Sol - 8 Sol